

PeopleLink iCam-650



PeopleLink iCam650 is a USB based Camera which supports resolution upto 640p with 650 TVL and 1x optical Zoom.

PTZ Cam



Specifications – PeopleLink iCam-650

IMAGE SENSOR	Sensor	1/4 Super HAD CCD
	Signal System	PAL/NTSC
	Illumination	1.0Lux/F1.6
	White Balance	Auto/Manual
	Gain Control	Auto
	Back-light	On / Off
	E-Shutter	1/50~1/10,000S
	S/N Ratio	>50dbS
LENS	Horizontal Resolution	650TVL
	Focus	f=5.0-90mm, F1.6-3.0
	Iris	Auto/Manual
	Zoom	18x Optical
Video Output	VBS: 1.0Vpp at 75 Ohm, S-Video ,USB Output	
Control Decoder	Built-in decoder	
Communication Interface	EIA/RS485,EIA/RS422, EIA/RS232 (Bidirectional)	
PTZ Control Protocol	VISCA, PELCO-P, PELCO-D (optional)	
Baud Rate	4800/9600bps	
Patrol Lines	4 Patrol Lines	
Preset Position	64 Preset Position	
Power-off Protection	Saved scanning or patrol line settings Automatically Before power off	
OSD Menu	To change parameters of camera or camera module from OSD Menu	
Image Auto Flip	Auto Flip	
Pan Speed	1-280 degree per second	
Tilt Speed	1-100 degree per second	
Pan Rotation Angle	360 degrees continuously	
Tilt Rotation Angle	240 degrees	
Auto Pan Scan	Support auto pan scanning	
Boundary Scan	0-359 degree (programmable)	
Remoter Control	IR wireless remote controller P/T/Z	
Power Supply	DC12V±10%, 1.2A	
Working Temperature	0-50	
Environment Humidity	0-95%RH	
Size(LxWxH)	250mm x 140mm x 154mm	
Weight	1380g	

Ideal for 15-25

Participants depending on the Room Size



HD Video Conferencing & Telepresence

www.peoplelink.in

Global Headquarters:

Q-3, A-3, 10th Floor, Cyber Tower
Hitech City, Madhapur,
Hyderabad - 500 081 - INDIA.
Tel: +91-40-44751111 to 32
Fax: +91-40-44751136

For Support:

INDIA - Tel: +91-40-44751116 to 17
USA - Tel: 16265000033 & 12014936974
CANADA - Tel: 16478482515 & 16478482516
UK - Tel: 442033551897
Email: support@peoplelink.in