

PeopleLink iCam-250



Image Sensor: CCD : 1/4" SONY CCD, Minimum Scene Illumination : 0.05 Lux
White Balance : AUTO/Manual, Gain Control : Auto, Back-light Compensation : On/Off
Electronic shutter : 1/50-1/10,000s, Horizontal resolution : 470-530 TVL, S/N Ratio : > 50dB
Lens: Focus : AUTO, Iris : AUTO/Manual, Zoom : 10 Optical, Zoom, f=3.9-39 mm,F1.8-F2.9
Video Output: VIDEO VBS 1.0Vpp at 75ohm; S-VIDEO
Communication : EIA/RS-422, EIA/RS-232 Bidirectional
Baud Rate : 2400/4800/9600 bps
Patrol tours : 4
Pattern tours : 4
Preset : 64
Privacy Mask Zone :4
Power On Active : Auto pan scan or Patrol Programmable
Speed Matching Function : Support
OSD Menu : Support
Image Auto Flip: Support
Pan Speed : 0-280 degrees/s
Tilt Speed : 0-100 degrees/s
Pan rotation angle: 360 degrees continuously
Tilt rotation angle : 180 degrees
Auto Pan Scan : Supports
Boundary Scan : 0-359 degrees (programmable)
Remoter Control : F Wireless remote control P/T/Z (10M)
Power : DC 12v+-10% 1.2A
Temperature and humidity: 0o-60oC 0-95% RH (non-condensation)