

# PeopleLink-e-Podium



e-Podium



A Product of PeopleLink Corporate Solutions Pvt Ltd.  
An ISO 9001:2008 Certified Company  
[www.Peoplelink.in](http://www.Peoplelink.in)

# Specifications – PeopleLink-e-Podium

<b>The whole set of equipment composition :</b>	1. Table Body 2. 19"LCD Touch Monitor 3. Center Controller system and the 7"controller panel 4. Digital Amplifier 5. wireless microphone	
<b>1. BODY S900</b>	Material	Arylic, stainless steel and solid wood
	Sliding cover	Opening/Closing the cover easily
	Adjusting Monitor Angle system (Actuator)	User can set monitor's angle
	Dimension	Size:890*675*1100mm (L*W*H)
	Laptop Interface Modules	VGAX1, USBX1, VIDIO X1, NETX1,ADIO X1
	Power distributor	AC Outputs:220V-240V AC, 50Hz/60Hz Maximum Input Power: 3KW
<b>2.19" LCD Touch Monitor</b>	Luminance	300cd/m2
	Contrast Ratio	1000 : 1
	Resolution	1440 x 900
	Response time (ms)	5ms
	Power supply	12V 4A AC adapter
	Viewing Angles	170(H);160(V)
	Technology	Touch panel of resistance
	Interface	USB/VGA/DC12V
Durability	30 million times touch validity	
<b>3. Multimedia Controller System</b>	<b>Pattern NO. : Y750</b>	
<b>VGA</b>	VGA X 3	
	VGA Outputs	VGA X 2
	Signal Type	VGA, XGA
	Max. Resolution	2048 X 1536
	Pixel Frequency	440MHz
<b>Video</b>	Composite Inputs	Video X 4
	Composite Output	Video X 2
	Bandwidth	100MHz
	Return loss	—30dB; 5MHz
<b>Control</b>	Switch Control Ports	X 2
	Screen Relay Controls	X 2
	Serial RS-232 Ports	X 1
<b>Other</b>	Power(Adaptor)	12V, 4A
	Weight	1.5Kg
<b>7 inch Controller panel</b>	Controller panel separated with the host	
	High voltage control module: the power of projectors and screens lifting	
	Computer automatic switch machine button	
	Volume and tone control module	
	Light touch glass panel with a backlight	
<b>4. Digital Amplifier</b>	<b>Pattern NO. : G325</b>	
<b>Output Power (Max)</b>	4*80W/8Ω 4 *160W/4Ω	
<b>Microphone Inputs</b>	8~20mV (3 Input)	
<b>PC/Laptop Inputs</b>	70mV (2 Input)	
<b>Audio Inputs</b>	70mV (4 Input)	
<b>Audio Outputs</b>	250mV (3 Output)	
<b>Frequency Response</b>	25Hz ~ 20KHz	
<b>AC Power</b>	220V to 240V AC, 20Hz/20kHz	
<b>Dimensions</b>	103(H) x 300(W) x 485(D) mm	
<b>Weight</b>	4.8 Kg	
<b>5. wireless microphone</b>	<b>Pattern NO. : UA-78</b>	
<b>Package:</b>	Aluminum box packaging	
<b>Frequency range:</b>	174-270MHZ;	
<b>Frequency response:</b>	60HZ-16KHz+-3dB	
<b>Power supply:</b>	DC-16V	
<b>Size (MM):</b>	480 (L) *190 (W) *44 (H)	

## Global Headquarters:

Q-3, A-3, 10<sup>th</sup> Floor, Cyber Tower  
Hitech City, Madhapur,  
Hyderabad - 500 081 - INDIA.  
Tel: +91-40-44751111 to 32  
Fax: +91-40-44751136

## For Support:

INDIA - Tel: +91-40-44751116 to 17  
USA - Tel: 1626500033 & 12014936974  
CANADA - Tel: 16478482515 & 16478482516  
UK - Tel: 442033551897  
Email: support@peoplelink.in